


TECHNICAL DATA SHEET

LEADERS IN CORROSION PREVENTION & SEALING TECHNOLOGY



Premier PVC Self-Adhesive Tape 250

Composition

Premier PVC Self-Adhesive Tape 250 consists of a PVC film coated on one side with self-adhesive.

Uses

Premier PVC Self-Adhesive Tape 250 is a selfadhesive tape used as an outer layer to provide additional mechanical and UV protection to the Premtape range of anti-corrosion tapes.

Service Temperature: -5°C to +60°C with a shortterm peak at +80°C

Characteristics

Premier PVC Self-Adhesive Tape 250 is:

- highly conformable,
- highly elongated at break,
- suitable for hand application, and
- suitable for machine application.

Application

Wrap spirally over used Premtape, ensuring sufficient tension and overlap while avoiding creases and folds.

Application temperature: +5°C to +40°C

Testing

Ensure the application has:

- sufficient tension,
- no creases or folds, and
- sufficient overlap.

Availability

Premier PVC Self-Adhesive Tape 250 is available in silver coloured 33 metre rolls in widths from 50 mm to 225 mm.

Storage conditions

Store in a cool dry place in original packaging.

Waste material

Please apply the waste hierarchy to avoid or minimise waste wherever possible. Please do not discard waste material, including packaging, in the surrounding environment. Follow all relevant legislation for disposal.

Typical Properties

Thickness	0.25 mm	ASTM D1000
Weight	0.33 kg/m ²	
Tensile strength at break	5 N/mm	ASTM D1000
Elongation at break	150%	ASTM D1000
Tear strength	15 N	ASTM D1004
Adhesion Peel strength		
To self	0.4 N/mm	ASTM D1000
To steel	0.4 N/mm	
Dielectric strength (double layer)	20 kV minimum	ASTM D1000

Important: Premier Coatings Ltd. pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Premier Coatings Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. Q09303) and an Environmental Management System registered to BS EN ISO 14001 (BSI Certificate no. EMS 677780).

PREMIER COATINGS LTD Headcorn Road, Smarden, Ashford, Kent, TN27 8PJ United Kingdom



TEL: +44 (0) 1233 770 663 FAX: +44 (0) 1233 770 633 WEB: www.premiercoatings.com EMAIL: enquiries@premiercoatings.com

Revision date: 17/07/2024